

18 Watt - Series

Level VI

Desktop Type



ATS018T - □ X X X

P : C6 / C14 ← O / P Voltage
A : C8

Output	
Load Regulation	±5% (Typical)
Ripple	1 ~ 2% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	22AWG / 20AWG / 18AWG
Ferrite Core	No (Optional)

Safety Approvals	
CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM / LPS	

Electrical	
Topology	Switching Flyback
Dielectric Withstand	3,000 VAC Primary - Secondary
Leakage Current	0.25mA
Efficiency	DoE Level VI, Energy Star, ErP Stage 2, NRCAN & GEMS Level VI Certified
EMI Conduction & Radiation	Compliance to EN55022 Class B
Harmonic Current	Compliance to EN61000-3-2,3
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332

Environmental	
Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical	
Case Dimension	P : L100 x W50 x H33 (mm) A : L88 x W50 x H34 (mm)
Weight	144g (Ref.)

Green Mode
CEC, DoE Level VI, Energy Star, ErP Stage 2, NRCAN & GEMS Level VI
NO Load Power Consumption Less Than 0.1W

- Features :**
- 100-240VAC Universal Input
 - Single Output to 18W
 - Regulated Output With Low Ripple Noise
 - Safety Agency Requirements and EMI/EMS Certified
 - Private Label Marking Available
 - Modified and Custom Design Available
 - 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS018T-□050	5.0V	3.0A	15.00W
ATS018T-□060	5.9V	2.5A	14.75W
ATS018T-□061	5.9V	3.0A	17.70W
ATS018T-□070	7.0V	2.5A	17.50W
ATS018T-□075	7.5V	2.5A	18.75W
ATS018T-□090	9.0V	2.2A	19.80W
ATS018T-□100	10.0V	1.9A	19.00W
ATS018T-□110	11.0V	1.6A	17.60W
ATS018T-□120	12.0V	1.6A	19.20W
ATS018T-□150	15.0V	1.3A	19.50W
ATS018T-□160	16.0V	1.2A	19.20W
ATS018T-□180	18.0V	1.1A	19.80W
ATS018T-□240	24.0V	0.8A	19.20W

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	0.48A Max.
Protection	Internal Primary Current Fuse , Inrush Limiting
Configuration	IEC60320/C6,C8,C14

